



NMT-420

Full HD ATM Module Network Camera




Key Functions

- Auto Exposure, Auto White Balance
- Triple Stream(H.264, MPEG4, MJPEG)
- Onvif Profile S
- Easy Install : Zero Configuration, Discovery, PoE
- Event Boosting, FTP Image Upload, Web Casting, Open VPN, QoS, IP Filtering
- Cross Web Browsing(IE, Safari, Firefox, Chrome)
- Privacy Masking
- AiHM Event
- Event Buffering

Software

- SmartManager
- NC-Titanium
- Tive HD
- Titanium Plus VMS

Dimension



Key Features

- Full HD(1920x1080) Resolution
- 4.3mm Fixed Lens(F=2.5)
- Alarm Input(1), Alarm Output(1)
- SD Card Up to 32GB
- PoE, 12VDC

Technical Specifications

Model	NMT-420	
IMAGE		
Lens	Fixed-Focal 4.3mm Pin Hole, F2.0	
Angle of View	75°(H)	
Image Sensor	Type	1/2.8"SONY Exmor CMOS Sensor
	Pixels	2,000(H)x1,241(V)
Min. Illumination	Color : 1.0 Lux@F2.0 50IRE	
Scanning Mode	Progressive Scan	
Wide Dynamic Range	Digital WDR(ATR-EX)	
Noise Reduction	2DNR	
Digital Zoom	Yes(ROI)	
Exposure Control	Auto, Hold Current	
White Balance Control	Auto, Incandescent, Fluorescent, Outdoor	
Back Light Compensation	Yes	
Image Effect	Flip, Mirror	
Flicker Free Mode	50Hz, 60Hz	
Shutter Speed	Auto(1/10,000~1/60sec, 1/15, 1/8, 1/4 Slow Shutter), Manual	
VIDEO/AUDIO		
Compression	H.264(Baseline, Main, High Profile), MJPEG	
Bitrate Control	CBR, VBR	
Resolution	1920x1080, 1280x720/1024, 704x480/576, 640x480, 352x240/288, 320x240	
Frame Rate	Max. 25/30fps	
Streaming	Max. 25/30fps(Triple Stream : H.264x2, MJPEGx1)	
Audio Compression	G.711	
Audio Streaming	2 Way	
SYSTEM		
Audio Streaming	2 Way	
Motion Detection Area	16 Programmable Area(Include Area 8, Exclude Area 8)	
Privacy Mask Zone	8 Programmable Zone	
FTP Uploading	MJPEG	
Event Notification	E-mail, FTP, Notification Server, XML Notification, Audio Alert, AiHM	
Audio Alert	User-Defined 3 Audio files	
Login Authority	Administrator, Operator, Guest	
Event Buffering	FTP	Pre : 30sec, Post : 30sec
	SD Record	Pre : 10sec, Post : 60sec
Manual Trigger	4 Programmable Trigger	
Security	Multi User Authority, IP Filtering, HTTPS, SSL	
Network Time Sync	NTP Server, Synchronized Computer, Manual	
Software Reset	Restart, Reset, Factory Default	
Hardware Factory Reset	Yes	
Auto Recovery	Backup, Restore	
Remote Upgrade	Web Browsing(IE, Chrome, Safari, Firefox), SmartManager, NC-Titanium	
SD Recording Mode	Event, Continuous	
NETWORK		
Protocol	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, QoS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour	
Client Software	Web, SmartManager, NC-Titanium, Tive HD	
Max. User Connection	Live : 10 Users, Playback : 3 Users	
API Support	Open API, Onvif Compliance	
Mobile Support	Tive HD(Android, iOS)	
EXTERNAL IN/OUT		
Audio	1 Input, 1 Output(Terminal Block)	
Alarm	1 Input, 1 Output(EXT. Cable)	
Ethernet	RJ-45(10/100Base-T)	
u-SD Card	SDHC(Max. 32GB)	
ETC		
Operating Humidity	0~90% RH(Non-Condensing)	
Operating Temperature	-10~+50 °C	
Power Supply	PoE(IEEE802.3af compliance, Class0), 12VDC	
Power Consumption	88mA(4.0W)@PoE 330mA(4.0W)@12VDC	
Dimension	47(W)x115(H)x32(T)mm	
Net Weight	110g	

Specifications are subject to change without notice.