



NTH-12J2

2MP IR Motorized Turret Network Camera

Key Features

- H.265, H.264 Support
- 2MP Resolution
- Motorized Varifocal 2.8~12mm Lens
- True Day & Night
- WDR(ATR-EX)
- 30 IR LEDs for 30m Coverage
- PoE
- IP66

Technical Specifications

Model	NTH-12J2	
IMAGE		
Lens	Motorized Varifocal 2.8~12mm F1.4	
Angle of View	94°(H)~34°(H)	
Image Sensor	Type	1/2.9" Sony Exmor CMOS
	Pixels	1984(H)x1125(V)
Min. Illumination	Color : 0.1Lux@F2.1 / BW : 0Lux@F2.1(IR LED On)	
Scanning Mode	Progressive Scan	
Wide Dynamic Range	Yes	
Day and Night Mode	True D/N(Auto, Day, Night)	
Noise Reduction	2DNR, 3DNR	
Digital Zoom	ROI	
Exposure Control	Auto	
White Balance Control	Auto, Manual	
Back Light Compensation	Yes	
Image Effect	Flip, Mirror, Defog	
Flicker Free Mode	50Hz, 60Hz	
Shutter Speed	Auto(1/10,000~1sec), Manual	
IR Illuminator	Quantity	30 IR LEDs
	Angle	90/30°(H)
	Distance	30m
VIDEO/AUDIO		
Compression	H.264(Baseline, Main, High Profile), MJPEG	
Bitrate Control	CBR, CVBR	
Resolution	1920x1080, 1280x1024, 1280x720/960, 1024x768, 704x480/576, 640x480, 320x240	
Frame Rate	Max. 30/25fps(NTSC/PAL)	
Streaming	Triple Stream : H.264/H.265x2, MJPEGx1	
SYSTEM		
Video Contents Analysis	Tampering	
Motion Detection Area	16 Programmable Area(Include Area 8, Exclude Area 8)	
Privacy Mask Zone	4 Programmable Zone	
Smart Codec ROI	8 Regions	
FTP Uploading	MJPEG	
Event Notification	E-mail, FTP, Notification Server, XML Notification	
Login Authority	Administrator, Operator, Guest	
Event Buffering(FTP)	Pre : 30sec, Post : 30sec	
Manual Trigger	4 Programmable Trigger	
Security	Multi User Authority, IP Filtering, HTTPS, SSL	
Network Time Sync	NTP Server, Synchronized Computer, Manual	
Software Reset	Restart, Reset, Factory Default	
Auto Recovery	Backup, Restore	
Remote Upgrade	Web Browsing(IE, Chrome, Safari, Firefox), SmartManager	
NETWORK		
Protocol	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, QoS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour	
Client Software	Web, SmartManager, Client S/W, Mobile S/W	
Max. User Connection	Live : 10 Users, Playback : 3 Users	
API Support	Open API, Onvif Compliance	
Mobile Support	Android, iOS	
EXTERNAL IN/OUT		
Video Composite Out	-	
Audio	-	
Alarm	-	
Ethernet	RJ-45(10/100Base-T)	
u-SD Card	-	
ETC		
Operating Humidity	95% or less(Non-Condensing)	
Operating Temperature	-20~+50°C	
Power Supply	PoE/12VDC	
Power Consumption	175mA(8.4W)@PoE / 550mA(6.6W)@12VDC	
Dimension	135.4(Ø)x127.7(H)mm	
Net Weight	Approx. 900g	
Ingress Protection	IP66	


Key Functions

- Smart Codec
- Tampering
- Triple Stream(H.264/H.265, MJPEG)
- Onvif Profile S
- Easy Install : Zero Configuration, Discovery, PoE
- Multi User Authority, IP Filtering, HTTPS, SSL
- Cross Web Browsing(IE, Safari, Firefox, Chrome)
- Privacy Masking

Software

- SmartManager
- Titanium 2.0
- Titanium Mobile

Dimension



Specifications are subject to change without notice.